

Migration guide

Esup Lecture Portlet - Migration Guide

!logoCLectureV1.jpg|width=32,height=32!Auteur : Bourges Raymond - Bouteille Gwénaëlle - Vincent Repain ([University of Rennes 1](#))

- [Esup Lecture Portlet - Migration Guide](#)
- [From 1.5.1 to 1.5.2](#)
- [From 1.2.x or 1.3.x to 1.5.1](#)
- [From 1.2.7-1.2.8 to 1.3.0](#)
- [From 1.2.5-1.2.6 to 1.2.7](#)
 - [Use of thickbox :](#)
 - [Use of js-layout :](#)
- [From 1.2.4 to 1.2.5](#)

From 1.5.1 to 1.5.2

- Download esup-lecture-1.5.2.zip from [the projectsite](#)
- Unzip the file in the parent directory of the 1.5.2 directory.
- Recover the files from previous version :
 - ant recover-config
- Deploy the application:
 - **ant deploy**
- Start the "esup-lecture" context on all application servers

From 1.2.x or 1.3.x to 1.5.1

- Download esup-lecture-1.5.1.zip from [the projectsite](#)
- Unzip the file in the parent directory of the 1.5.1 directory.
- Recover the files from previous version :
 - ant recover-config
 - NOTE:
 - properties/esup-lecture.dtd has been modified since previous version and should not be recovered
 - properties/domain/domain.xml has been modified since previous version and should not be recovered
- Verify the configuration files
 - New parameters are now accepted and may be used in esup-lecture.xml: See [Changelog](#) and [Installation guide](#)
- Stop the "esup-lecture" context on all application servers
- SAVE the esup-lecture database
- Run **ant upgrade**
- Deploy the application:
 - **ant deploy**
- Start the "esup-lecture" context on all application servers

From 1.2.7-1.2.8 to 1.3.0

- Download esup-lecture-1.3.0.zip from [the projectsite](#)
- Unzip the file in the parent directory of the 1.3.0 directory.
- Recover the files from previous version :
 - ant recover-config
 - NOTE : esup-lecture.dtd has been modified since previous version and should not be recovered
- Verify the configuration files
 - New parameters are now accepted and may be used in esup-lecture.xml and <category>.xml :See [Changelog](#) and [Installation guide](#)
- Stop the "esup-lecture" context on all application servers
- SAVE the esup-lecture database
- Run ant upgrade
- If you want to keep old records of read items, initialize the new table of read items like this :
 - Open a database connexion with a SQL editor
 - Run the SQL command :
insert into LECT_READITEMFLAG (ELEMENTID, CUSTOMSOURCE_CUSTOMSOURCEPK, DATE) (select ITEMID, CUSTOMSOURCE_CUSTOMSOURCEPK, now() from LECT_READITEM)
 - (replace "now()" with the appropriate function or pseudocolumn according to your SGBD)
- Then, delete the old table of read items :
 - Open a database connexion with a SQL editor
 - Run the SQL command :
drop table LECT_READITEM;
- Deploy the application:
 - ant deploy
- Start the "esup-lecture" context on all application servers

From 1.2.5-1.2.6 to 1.2.7

- Download esup-lecture-1.2.7.zip from [the projectsite](#)
- Unzip the file in the parent directory of the 1.2.7 directory.
- Adapt build.properties in the previous version directory to recover some configuration files from that version : edit the **custom.recover.files**, for example :

```
custom.recover.files= \
properties/mappings.xml \
properties/logging/log4j.properties
```

- Recover the files from previous version :
 - ant recover-config

Use of thickbox :

Thickbox library is provided with this package. To use it :

- Make sure that the following tags are listed in the "script" section of tags/tags.xml :
 - <value>js/jquery.js</value>
 - <value>js/thickbox.js</value>
- Add a "thickbox" class to the anchor tab in the mapping file used by the source. An example file is provided in properties/mappings.xml, you may download and adapt it to your own needs.

More informations about thickbox : <http://jquery.com/demo/thickbox/>

Use of js-layout :

Js-layout library is provided with this package and is automatically used in configurations with two panels.

- Make sure that the following tags are listed in the "script" section of tags/tags.xml :
 - <value>js/jquery.layout.js</value>
 - <value>js/init-js-layout.js</value>

More informations about js-layout : <http://layout.jquery-dev.net/>

- Deploy the application:
 - ant deploy

From 1.2.4 to 1.2.5

- Download esup-lecture-1.2.5.zip from [the projectsite](#)
- Unzip the file in the parent directory of the 1.2.4 directory.
- Adapt build.properties in the 1.2.4 directory to recover some configuration files from that version : edit the **custom.recover.files**, for example :

```
custom.recover.files= \
properties/mappings.xml \
properties/logging/log4j.properties
```



Do not list propertie/dao/dao.xml in the files to recover, as this file has been modified in version 1.2.5

- Recover the files from version 1.2.4 :
 - ant recover-config
- Add **hibernate.connection** parameters (jdbc and jndi) in **config.properties** (new in 1.2.5, see config-example.properties)



by default (see defaults.properties), esup-lecture use a jndi connection. If you want instead an jdbc connection, add in **config.properties** : hibernate.useJdbc=true

- Deploy the application:
 - ant deploy

